



1755

Air

Long Case

Protect your long equipment inside the world's toughest and lightest case. The Pelican™ Air Case 1755 is the longest Air case at 55" in length. With built in wheels and less weight than other polymer cases, the Pelican™ Air Case 1755 keeps you rolling along. It is ideal to protect survey equipment, firearms, camera tripods and other lengthy equipment.

With 12 bosses in the lid, the Pelican™ Air Case 1755 can fit up to three exclusive Pelican™ Ez-Click™ MOLLE Panels for lid organization. Pre-configure your gear by pairing a MOLLE panel with a variety of MOLLE pouches and Velcro™ straps (sold separately). Easily attach your configured MOLLE panels to the inside of your case lid and you are ready for your job or adventure.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- 55" x 14" x 8" Interior space - the longest AIR case
- 2-hand XL over-molded top handle
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels



CONFIGURATIONS



1755
Standard



1755WF
With Foam



1755NF
No Foam


DIMENSIONS

Interior (LxWxD)	55.00 x 14.00" x 8.00 (139.7 x 35.6 x 20.3 cm)
Exterior (LxWxD)	57.82 x 17.30" x 8.86 (146.9 x 43.9 x 22.5 cm)
Lid Depth	2.50" (6.4 cm)
Bottom Depth	5.50" (14 cm)
Total Depth	8" (20.3 cm)
Int Volume	3.56 ft ³ (0.101 m ³)
Padlock Hole Diameter	0.42" (1.1 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	EPDM
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven
Handle	PP with TPE

COLORS

 Black

WEIGHT

Weight With Foam	25.00 lbs (11.3 kg)
Weight Empty	20.00 lbs (9.1 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

ACCESSORIES




1500MP
EZ-Click™ MOLLE Panel



1500CI
Corrosion Intercept Kit



1755AirFS
4 pc. Replacement Foam Set



LGMT-001A
Air Case Roof Mount

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-08-24