



1700

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3-piece foam set
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Hi-density foam tray option for 10 firearms
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



CONFIGURATIONS



DIMENSIONS

Interior (L×W×D)	35.76 x 13.73" x 5.35 (90.8 x 34.9 x 13.6 cm)
Exterior (L×W×D)	38.47 x 16.42" x 6.14 (97.7 x 41.7 x 15.6 cm)
Int Volume	1.52 ft³ (0.043 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Desert Tan	 OD Green
---	--	--

WEIGHT

Weight With Foam	16.85 lbs (7.6 kg)
Weight Empty	15.10 lbs (6.8 kg)







TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

OTHER

Military	yes
-----------------	-----

ACCESSORIES

				
1500MP EZ-Click™ MOLLE Panel	1500CI Corrosion Intercept Kit	1506TSA TSA Lock	1500D Desiccant Silica Gel	1703 Replacement O-ring
				
LGMT-001P Protector Case Roof Mount				