

1495CC1

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\rm m}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- 3 dial combination lock included
- Fits up to 17" laptops
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lid organizer, shock absorbing tray, and padded shoulder strap
- Nylon padded computer sleeve and accessories pouch
- Stainless steel padlock protectors



DIMENSIONS

Interior (L×W×D) 18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm) Exterior (L×W×D) 21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm)

 Lid Depth
 1.12" (2.8 cm)

 Bottom Depth
 2.68" (6.8 cm)

 Total Depth
 3.8" (9.7 cm)

 Int Volume
 0.55 ft³ (0.016 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 11.10 lbs (5 kg)

 Buoyancy
 45.15 lbs (20.5 kg)

 Master Pack Weight
 28.00 lbs (12.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack2Nameplateyes

ACCESSORIES



1483 Replacement O-ring



1495ALI Attache/Computer Lid Insert



1495CBIComputer Bottom Insert



1495HDF 4 lb. High Density Foam



1506TSA TSA Lock



1500D Desiccant Silica Gel



1500CICorrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-09-24