

# 1610M Protector Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican <sup>TM</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane
- wheels with stainless steel bearings
- Water resistant, crushproof, and dust resistant

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



### CONFIGURATIONS



**1610M** Standard



1610MNF No Foam



1610MWF With Foam

#### DIMENSIONS

| Interior (L×W×D)      | 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)   |
|-----------------------|--|
| Exterior (L×W×D)      | 26.20 x 23.00" x 13.68 (66.5 x 58.4 x 34.7 cm) |
| Lid Depth             | 2.05" (5.2 cm)                                 |
| Bottom Depth          | 8.57" (21.8 cm)                                |
| Total Depth           | 10.62" (27 cm)                                 |
| Int Volume            | 2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )   |
| Padlock Hole Diameter | 5/16" (12.7 cm)                                |

# MATERIALS

| Body       | Polypropylene                  |
|------------|--------------------------------|
| Latch      | ABS                            |
| O-Ring     | Polymer                        |
| Pins       | Stainless Steel                |
| Foam       | 1.3 lb Polyurethane            |
| Purge Body | ABS                            |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |
|            |                                |

### COLORS

Black

### WEIGHT

| Weight With Foam | 29.10 lbs (13.2 kg) |
|------------------|---------------------|
| Weight Empty     | 26.30 lbs (11.9 kg) |

### TEMPERATURE

| Minimum Temperature | -40°F (-40 °C)  |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

### CERTIFICATIONS

#### IP57

#### OTHER

| Wheels            | 2   |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack       | 1   |
| Nameplate         | yes |
| Military          | yes |

# ACCESSORIES



**1609** Lid Organizer



**1507** Quick Mounts - set of 4



**1611** 5 pc. Replacement Foam Set



**1506TSA** TSA Lock



**1612** Pick N Pluck<sup>™</sup> Sections Only (set of 3)



**1500D** Desiccant Silica Gel



1615 Padded Divider Set



**1500Cl** Corrosion Intercept Kit



1623 Replacement O-ring



**1610MP** EZ-Click<sup>™</sup> MOLLE Panel

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-09-24