

1607 _{Air}

Pelican[™] Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 45 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican[™] Air line of cases, we're redefining the future

With the launch of the Pelican[™] Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

 $\mbox{ \bullet}$ Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull[™] Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²[™] Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Made in the USA



CONFIGURATIONS



1607 Standard



1607NF No Foam



1607WD With Padded Dividers



1607WF With Foam

DIMENSIONS

Interior (L×W×D)	21.05 x 15.81" x 11.63 (53.5 x 40.2 x 29.5 cm)
Exterior (L×W×D)	24.13 x 18.80" x 13.25 (61.3 x 47.8 x 33.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.60" (24.4 cm)
Total Depth	11.6" (29.5 cm)
Int Volume	2.24 ft ³ (0.063 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

BodyProprietary Polypropylene BlendLatchABSO-RingEPDMPurge BodyABS

Purge Vent

COLOURS

Black	Orange	Silver	Yellow	
WEIGHT				
Weight With Foam	16.10 lbs (7.3 kg)			
Weight Empty	13.20 lbs (6 kg)			
Buoyancy	178.00 lbs (80.7 kg)			

Minimum Temperature-60°F (-51.1 °C)Maximum Temperature160°F (71.1 °C)

2

OTHER

Wheels

ACCESSORIES



Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 07-17-24