



## 3325

**Compact / Safety Certified / Tail Switch Design** - All three are combined in the 3325 LED flashlight. The compact and lightweight design begins with the use of only 3 AA alkaline batteries and yet produces over 162 lumens of brilliant light. Safety certified for use in most volatile work environments. The rear mounted switch makes the 3325 a perfect match for any helmet mounted applications. The photoluminescent ("glow in the dark") shroud ensures you'll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325 in the most severe weather conditions. Backed by Pelican's Lifetime Guarantee makes the 3325 a true value!

- 3 AA Batteries (Included)
- Glow-in-the-dark shroud
- Tail switch for easy one-handed operation
- Pelican Products, Inc.'s Lifetime Guarantee
- Ingress Protected IPX7
- Class I, Class II, Class III - Division 1 Safety Certified



### DIMENSIONS

---

**Length** 6.06" (15.4 cm)


### MATERIALS

---

**Body** EXL  
**O-Ring** EPDM  
**Lens** Polycarbonate (PC)  
**Shroud** Photo luminescent Polycarbonate (PC)

### COLOURS

---

 High Visibility Yellow

### LIGHT SPECS

---

**Lamp Type** LED

### POWER

---

**Battery Size** AA  
**Battery Type** Alkaline  
**Battery Quantity** 3  
**Batteries Included** yes  
**Volts** 4.5v

### WEIGHT

---

**Weight With Batteries** 6.1 oz (173 gr)  
**Weight Without Batteries** 3.6 oz (102 gr)

## SWITCH

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
Push Button  
**Switch Type**  
**Light Modes** On / Off  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)






Document created on 07-17-24

## CERTIFICATIONS

**Class I, Division 1**  
**IECEX ia**  
**Class II, Division 1**  
**Class III, Division 1**

## OTHER

**Minimum Pack** 1  
**Package Code** C

FL1 STANDARD	HIGH
	171 LUMENS
	16h 0mins
	136m
	4558cd
	IPX7

## ACCESSORIES