



# 1030

## Micro

From small sensitive components to smartphones, protect your gear from the elements in a crushproof, watertight, & dustproof Micro Case from Pelican.

- **\*Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Carabiner
- Easy open latch
- Lifetime Guarantee of Excellence
- Rubber liner for extra protection doubles as o-ring seal
- Stainless steel hardware






### DIMENSIONS

<b>Interior (LxWxD)</b>	6.37 x 2.62" x 2.06 (16.2 x 6.7 x 5.2 cm)
<b>Exterior (LxWxD)</b>	7.50 x 3.87" x 2.43 (19.1 x 9.8 x 6.2 cm)
<b>Lid Depth</b>	0.69" (1.8 cm)
<b>Bottom Depth</b>	1.25" (3.2 cm)
<b>Total Depth</b>	1.94" (4.9 cm)
<b>Int Volume</b>	0.02 ft <sup>3</sup> (0.001 m <sup>3</sup> )

### MATERIALS

<b>Body</b>	Polycarbonate (PC)
<b>Latch</b>	Xylex
<b>O-Ring</b>	Thermoplastic Rubber
<b>Pins</b>	Stainless Steel
<b>Foam</b>	TL - 426 4 lb. Esther
<b>Purge Body</b>	Polycarbonate (PC)
<b>Purge Vent</b>	Polyester Spun-Bond ePTFE Oleophobic

### COLOURS

 Black	 Black - Clear	 Yellow - Clear
---	---	--

### WEIGHT

<b>Weight With Foam</b>	0.61 lbs (0.3 kg)
<b>Weight Empty</b>	0.60 lbs (0.3 kg)
<b>Buoyancy</b>	0.99 lbs (0.4 kg)
<b>Master Pack Weight</b>	4.24 lbs (1.9 kg)

### TEMPERATURE

<b>Minimum Temperature</b>	-10°F (-23.3 °C)
<b>Maximum Temperature</b>	199°F (92.8 °C)

## CERTIFICATIONS

---

**IP67**

## OTHER

---

<b>Minimum Pack</b>	6
<b>Master Pack</b>	6
<b>Military</b>	yes

## ACCESSORIES

---



**1031**  
Replacement Case Liner



**1032**  
Pick N Pluck™ Foam Insert

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 07-17-24*