



472-DELL-MON-22

Mobile IT™

Monitor Case

- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Vortex™ Valve
- Telescoping Handle
- Flush Powerful Hinges



DIMENSIONS

| | |
|-------------------------|--|
| Interior (L×W×D) | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| Exterior (L×W×D) | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 8.50" (21.6 cm) |
| Total Depth | 10.5" (26.7 cm) |
| Int Volume | 3.17 ft ³ (0.09 m ³) |

MATERIALS

| | |
|-------------------------|--|
| Body | Injection Molded HPX™ high performance resin |
| Latch | Valox - Polybutylene Terephthalate (PBT) |
| Latch (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring | Silicone Sponge |
| Pins | Stainless Steel |
| Foam | 1.3/1.35 polyester |
| Purge Body | Valox - Polybutylene Terephthalate (PBT) |
| Purge Body (Alt) | Xenoy - Polyester/Polycarbonate blend |
| Purge Vent | Gortex membrane |

COLOURS

| | | | |
|---|--|--|--|
|  Black |  Desert Tan |  Gray |  OD Green |
|---|--|--|--|

WEIGHT

| | |
|---------------|-------------------|
| Weight | 28.70 lbs (13 kg) |
|---------------|-------------------|

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C) |

OTHER

| | |
|--------------------------|-----|
| Wheels | 2 |
| Extendable Handle | yes |

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-17-24