



1700

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3-piece foam set
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Hi-density foam tray option for 10 firearms
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



CONFIGURATIONS



1700
Standard

1700WF
With Foam

1700NF
No Foam

DIMENSIONS

Interior (L×W×D)	35.76 x 13.73" x 5.35 (90.8 x 34.9 x 13.6 cm)
Exterior (L×W×D)	38.47 x 16.42" x 6.14 (97.7 x 41.7 x 15.6 cm)
Int Volume	1.52 ft ³ (0.043 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

■ Desert Tan

■ OD Green

WEIGHT

Weight With Foam 16.85 lbs (7.6 kg)

Weight Empty 15.10 lbs (6.8 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

OTHER

Military yes

ACCESSORIES



1500MP
EZ-Click™ MOLLE Panel



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1703
Replacement O-ring

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-17-24