

1770

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Also available from Pelican: The 1740 Long Case
- Four extra-deep base-to-lid locking cleats that ensure maximum stacking stability
- · Watertight, crushproof, and dustproof
- 4-piece foam set
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core, polymer wall construction
- Stainless steel hardware and padlock protectors
- Two Integrated Automatic Pressure Equalization Valves
- Two rugged double-wide handles
- · Wide-track polyurethane wheels with ball bearings and nylon hubs
- Comfortable rubber over-molded side-carry handle



CONFIGURATIONS







1770NF No Foam



1770WF With Foam

DIMENSIONS

 Interior (L×W×D)
 54.58 x 15.58" x 8.63 (138.6 x 39.6 x 21.9 cm)

 Exterior (L×W×D)
 57.42 x 18.48" x 11.23 (145.8 x 46.9 x 28.5 cm)

 Lid Depth
 1.88" (4.8 cm)

 Bottom Depth
 6.75" (17.1 cm)

 Total Depth
 8.63" (21.9 cm)

 Int Volume
 4.25 ft³ (0.12 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS O-Ring EPDM

Pins Stainless Steel

Purge Body AB

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 41.49 lbs (18.8 kg)

 Weight Empty
 36.01 lbs (16.3 kg)

 Buoyancy
 280.00 lbs (127 kg)

 Master Pack Weight
 39.50 lbs (17.9 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

1

OTHER

Master Pack

ACCESSORIES



1771 4 pc. Replacement Foam Set



1773 Replacement O-ring



1630DCDocument Container
Accessory



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

Document created on 07-17-24