

# 1400 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
  Stainless steel hardware
- Stainless steel padlock protectors



## CONFIGURATIONS



1400 Standard



1400NF No Foam



1400WF With Foam

## DIMENSIONS

| Interior (L×W×D)      | 11.81 x 8.87" x 5.18 (30 x 22.5 x 13.2 cm)   |
|-----------------------|--|
| Exterior (L×W×D)      | 13.37 x 11.62" x 6.00 (34 x 29.5 x 15.2 cm)  |
| Lid Depth             | 1.18" (3 cm)                                 |
| Bottom Depth          | 4.00" (10.2 cm)                              |
| Total Depth           | 5.18" (13.2 cm)                              |
| Int Volume            | 0.31 ft <sup>3</sup> (0.009 m <sup>3</sup> ) |
| Padlock Hole Diameter | 0.31" (0.8 cm)                               |

#### MATERIALS

| Body       | Polypropylene       |
|------------|---------------------|
| Latch      | ABS                 |
| O-Ring     | Polymer             |
| Pins       | Stainless Steel     |
| Foam       | 1.3 lb Polyurethane |
| Purge Body | ABS                 |

#### Purge Vent

## COLOURS



#### WEIGHT

| Weight With Foam   | 4.41 lbs (2 kg)     |
|--------------------|---------------------|
| Weight Empty       | 3.97 lbs (1.8 kg)   |
| Buoyancy           | 20.06 lbs (9.1 kg)  |
| Master Pack Weight | 22.60 lbs (10.3 kg) |

## TEMPERATURE

| Minimum Temperature | -40°F (-40 °C)  |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

### CERTIFICATIONS

| IP67           |  |  |  |
|----------------|--|--|--|
| MIL C-4150J    |  |  |  |
| Def Stan 81-41 |  |  |  |
| ATA 300        |  |  |  |
|                |  |  |  |

### OTHER

| Master Pack | 4   |
|-------------|-----|
| Nameplate   | yes |
| Military    | yes |

## ACCESSORIES



**1401** 3 pc. Replacement Foam Set



**1507** Quick Mounts - set of 4



1403 Replacement O-ring



**1506TSA** TSA Lock



1400PF Special Application Panel Frame



**1500D** Desiccant Silica Gel



**1400TPKIT** TrekPak Case Divider Kit



**1400TPDIV** Extra TrekPak Dividers

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-18-24