

# 1460 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- Personalized nameplate service available

• Top lid opens up to 180° for on-the-field anti-roll stability when open

• Watertight, crushproof, and dustproof

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- · Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



**1460** Standard



1460AALG With Custom Foam for 9430 / 9435



**1460NF** No Foam



**1460WF** With Foam

#### DIMENSIONS

Interior (L×W×D)	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (L×W×D)	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth	4.91" (12.5 cm)
Bottom Depth	6.01" (15.3 cm)
Total Depth	10.92" (27.7 cm)
Int Volume	1.16 ft <sup>3</sup> (0.033 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel

Foam	Polyurethane	
Purge Body	ABS	
Purge Vent	3 Micron Hydrophobic Non-Woven	

#### COLOURS

Black

### WEIGHT

Weight With Foam	12.48 lbs (5.7 kg)
Weight Empty	8.75 lbs (4 kg)
Buoyancy	82.00 lbs (37.2 kg)

#### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

#### CERTIFICATIONS

IP67

#### OTHER

Military

ACCESSORIES



**1461** 6 pc. Replacement Foam Set



yes

1463 Replacement O-ring



1507 Quick Mounts - set of 4

**1506TSA** TSA Lock

alai P bioi P bioi P



**1500D** Desiccant Silica Gel

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 04-30-24