



1610 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1610
Standard



1614
With Padded Dividers



1610NF
No Foam



1610TP
With TrekPak Divider System



1610WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm) |
| Exterior (L×W×D) | 24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm) |
| Lid Depth | 2.05" (5.2 cm) |
| Bottom Depth | 8.57" (21.8 cm) |
| Total Depth | 10.62" (27 cm) |
| Int Volume | 2.23 ft ³ (0.063 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

| | |
|---|--|
|  Black |  Desert Tan |
|---|--|

WEIGHT

| | |
|--------------------|----------------------|
| Weight With Foam | 22.30 lbs (10.1 kg) |
| Weight Empty | 19.50 lbs (8.8 kg) |
| Buoyancy | 119.93 lbs (54.4 kg) |
| Master Pack Weight | 25.55 lbs (11.6 kg) |

TEMPERATURE

| | |
|---------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |











CERTIFICATIONS

| |
|----------------|
| IP67 |
| Def Stan 81-41 |

OTHER

| | |
|-------------------|-----|
| Wheels | 2 |
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| 1609 Lid Organizer | 1611 5 pc. Replacement Foam Set | 1612 Pick N Pluck™ Sections Only (set of 3) | 1615 Padded Divider Set | 1623 Replacement O-ring |
|  |  |  |  |  |
| 1610TPKIT TrekPak Case Divider Kit | 1610TPDIV Extra TrekPak Dividers | 1507 Quick Mounts - set of 4 | 1506TSA TSA Lock | 1500D Desiccant Silica Gel |



1610MP
EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-06-24