



9415i

9410L + Safety = 9415i

Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 392 lumens, the 9415i LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 392 meters. And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety certified for the most volatile work areas, the 9415i LED Lantern is safe and one of the most compact, high output lanterns on the market.

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Carrying Strap included




DIMENSIONS

| | |
|--------|-----------------|
| Length | 8.75" (22.2 cm) |
|--------|-----------------|

MATERIALS

| | |
|--------|---------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | EPDM |
| Lens | Anti-static coated Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT |

COLOURS

| |
|--|
|  High Visibility Yellow |
|--|

LIGHT SPECS

| | |
|-----------|-----|
| Lamp Type | LED |
|-----------|-----|

POWER

| | |
|-------------------------|---------|
| Battery Size | C |
| Battery Type | NiMH |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Rechargeable | yes |
| Charge Time | 15 hrs |
| Battery Level Indicator | RGB LED |
| Volts | 4.8v |

WEIGHT

| | |
|--------------------------|-------------------|
| Weight With Batteries | 58.2 oz (1650 gr) |
| Weight Without Batteries | 0.0 oz (0 gr) |

SWITCH






| | |
|-------------|-----------------------|
| Switch Type | Push Button |
| Light Modes | High / Low / Flashing |

CERTIFICATIONS

| |
|-------------|
| IECEx ia |
| ATEX Zone 0 |
| InMetro |

OTHER

| | |
|--------------|---|
| Minimum Pack | 1 |
| Package Code | B |

| FL1 STANDARD | HIGH | LOW |
|---|------------|------------|
|  | 392 LUMENS | 144 LUMENS |
|  | 4h 30mins | 11h 0mins |
|  | 392m | 234m |
|  | 32767cd | 13747cd |
|  | IPX4 | |

ACCESSORIES



9416
Deck/Dash Charger Base Unit



6061F
Direct Wiring Rig for Fast Charger



8056F
12v Plug-in for Fast Charger



9418Z0
Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-01-24