



SUPER-V-SERIES-3U

Super V

3U

- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Choice of SAE 10-32 or Metric M6 clip nuts for even more flexibility in mounting equipment
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- High-strength steel rack frame supports equipment from 10 - 50 kg
- Designed to meet the requirements of Def Stan 81-41 Level J, Mil Standard 810, STANAG 4340 and other European standards.
- Designed to meet ANSI/EIA-310-C for universal rack mounting hole pattern
- 10 different models, frame heights 4-12U in two depths, 480 and 610mm
- Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHs compliant



DIMENSIONS

| | |
|--------------------------------|----------------------------------------------|
| Exterior (LxWxD) | 38.50 x 28.30" x 11.40 (97.8 x 71.9 x 29 cm) |
| Rack Height | 5.25" (13.3 cm) |
| Rack Depth | 24.00" (61 cm) |
| Interior Lid Depth | 2.20" (5.6 cm) |
| Interior Back Lid Depth | 5.20" (13.2 cm) |

MATERIALS

| | |
|-------------------|---------------------------------------------------|
| Body | RotoMolded Polyethylene |
| O-Ring | Silicone Sponge |
| Purge Body | Aluminum |
| Hardware | Stainless Steel (Black Oxide) / RoHs Nickel Black |
| Frame | Steel (Clear Coated) |

COLOURS

■ Black

WEIGHT

Weight 50.00 lbs (22.7 kg)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-17-24