

1700 Protector Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Strong polyurethane wheels with stainless steel bearings

- Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click[™] MOLLE Panels
- Hi-density foam tray option for 10 firearms
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



CONFIGURATIONS



1700 Standard

1700WF With Foam



1700NF No Foam

DIMENSIONS

| Interior (L×W×D) | 35.76 x 13.73" x 5.35 (90.8 x 34.9 x 13.6 cm) |
|-----------------------|---|
| Exterior (L×W×D) | 38.47 x 16.42" x 6.14 (97.7 x 41.7 x 15.6 cm) |
| Int Volume | 1.52 ft ³ (0.043 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| Body | Polypropylene |
|------------|--------------------------------|
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

| Black | Desert Tan | OD Green |
|--|--|----------|
| WEIGHT | | |
| Weight With Foam Weight Empty | 16.85 lbs (7.6 kg) 15.10 lbs (6.8 kg) | |
| TEMPERATURE | | |
| Minimum Temperature Maximum Temperature | | |

OTHER

Military

yes

ACCESSORIES



1500MP EZ-Click[™] MOLLE Panel





LGMT-001P Protector Case Roof Mount

1500CI Corrosion Intercept Kit



1506TSA TSA Lock



1500D Desiccant Silica Gel



1703 Replacement O-ring

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 07-17-24