

1595

Air

Designed for the professional adventurer, the 1595 Air case is perfect for those who need a little extra space without compromising on durability or weight. Sized between our popular 1535 Air carry-on case and the larger 1615 Air check-in case, the 1595 Air case offers the ideal solution for travelers seeking a lightweight and reliable option for their gear. Pelican™ Air cases are the toughest and lightest cases Pelican has to offer. Each Pelican Air case is up to 40 percent lighter than an average polymer case yet still extremely durable. Pelican Air cases will lighten the load, while protecting your valued possessions. With Pelican's trusted protection, you can travel with confidence.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- · Quiet rolling stainless-steel bearing wheels
- *Check with your airline for exact measurement requirements
- Press and Pull
 [™] Latches
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Waterproof O-ring seal
- · Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Limited Lifetime Warranty (Where applicable by law)
- Mid-size airline check-in case*



CONFIGURATIONS



1595 Standard



1595NF No Foam



1595WF With Foam



1595TPWith TrekPak Divider System

DIMENSIONS

Interior (L×W×D) 25.53 x 14.92" x 8.92 (64.8 x 37.9 x 22.7 cm) Exterior (L×W×D) 28.52 x 17.89" x 10.73 (72.4 x 45.4 x 27.3 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 6.92" (17.6 cm)

 Total Depth
 8.92" (22.7 cm)

 Int Volume
 1.97 ft³ (0.056 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Latch ABS O-Ring EPDM

PinsStainless SteelFoamPolyurethane

Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 16.35 lbs (7.4 kg)

 Weight Empty
 13.60 lbs (6.2 kg)

 Buoyancy
 148.37 lbs (67.3 kg)

 Weight With Organizers
 16.10 lbs (7.3 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & -60\,^{\circ}\mbox{F (-51.1 °C)} \\ \mbox{Maximum Temperature} & 160\,^{\circ}\mbox{F (71.1 °C)} \\ \end{array}$

ACCESSORIES



1500D Desiccant Silica Gel



1506TSA TSA Lock



1500CICorrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 07-17-24