

# 1620 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 4 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



# CONFIGURATIONS



1620 Standard



1624 With Padded Dividers



**1620NF** No Foam



1620WF With Foam

# DIMENSIONS

| Interior (L×W×D)      | 21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm) |
|-----------------------|--|
| Exterior (L×W×D)      | 24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm) |
| Lid Depth             | 2.01" (5.1 cm)                                 |
| Bottom Depth          | 10.53" (26.7 cm)                               |
| Total Depth           | 12.54" (31.9 cm)                               |
| Int Volume            | 2.56 ft <sup>3</sup> (0.072 m <sup>3</sup> )   |
| Padlock Hole Diameter | 0.31" (0.8 cm)                                 |

#### MATERIALS

| Body   | Polypropylene       |
|--------|---------------------|
| Latch  | ABS                 |
| O-Ring | Polymer             |
| Pins   | Stainless Steel     |
| Foam   | 1.3 lb Polyurethane |

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

# COLOURS

## WEIGHT

| Weight With Foam   | 24.62 lbs (11.2 kg) |
|--------------------|---------------------|
| Weight Empty       | 21.20 lbs (9.6 kg)  |
| Buoyancy           | 149.91 lbs (68 kg)  |
| Master Pack Weight | 26.90 lbs (12.2 kg) |

# TEMPERATURE

| Minimum Temperature | -40°F (-40 °C)  |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

# CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41

# OTHER

| Wheels            | 2   |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack       | 1   |
| Nameplate         | yes |
| Military          | yes |

# ACCESSORIES





**1507** Quick Mounts - set of 4



**1621** 6 pc. Replacement Foam Set



**1506TSA** TSA Lock



**1622** Pick N Pluck™ Sections Only (set of 4)



**1500D** Desiccant Silica Gel



1623 Replacement O-ring



**1610MP** EZ-Click<sup>™</sup> MOLLE Panel



1625 Padded Divider Set



1500CI Corrosion Intercept Kit

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 08-16-24