

1620M

Protector

Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{\tiny TM}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- \bullet 4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- · Water resistant, crushproof, and dust resistant
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS







1620MNF No Foam



1620WF With Foam

DIMENSIONS

Interior (L×W×D) 21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm) Exterior (L×W×D) 26.20 x 23.00" x 15.61 (66.5 x 58.4 x 39.6 cm)

 Lid Depth
 2.01" (5.1 cm)

 Bottom Depth
 10.53" (26.7 cm)

 Total Depth
 12.54" (31.9 cm)

 Int Volume
 2.56 ft³ (0.072 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 31.42 lbs (14.3 kg)

 Weight Empty
 28.00 lbs (12.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP57

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



1609 Lid Organizer



1621 6 pc. Replacement Foam Set



1622Pick N Pluck™ Sections Only (set of 4)



1623 Replacement O-ring



1625 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel



1500CICorrosion Intercept Kit



1610MP EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 07-17-24