



2410 StealthLite™

Our most demanding users wanted a safety-certified task light slim enough to fit in a pocket, but without sacrificing performance. We integrated a high-intensity, machined-aluminum LED module with a locking on/off toggle switch, which is ideal for operating with gloved hands. The 2410 represents a safety-certified task light with the compactness necessary for on-the-go tasks, but with all the performance and durability that you'd expect from Pelican. Same features as the StealthLite™ 2400 Flashlight, but with the LED module that produces a true, bright collimated LED beam. The 2410 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells (included).

- 4 AA Batteries Included
- Security Lanyard
- Rotational switch with locking on / off feature
- Compact, slender design
- Waterproof IPX7
- Lifetime Guarantee of Excellence



DIMENSIONS

Length	7.00" (17.8 cm)
--------	-----------------

MATERIALS

Body	EXL
O-Ring	Ethylene Propylene
Lens	Polycarbonate (PC)
Shroud	ABS
Contact Spring Retainer	Stainless Steel / Phosphore Bronze

COLOURS

 Black	 High Visibility Yellow
---	--

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	4
Batteries Included	yes
Volts	6.0v

WEIGHT

Weight With Batteries	7.3 oz (207 gr)
Weight Without Batteries	3.7 oz (105 gr)

8.4 oz (238 gr)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

SWITCH

Switch Type One-handed Safety Switch *Document created on 04-27-24*

Light Modes On / Off

CERTIFICATIONS

Class I, Division 1

Class II, Division 1

Class III, Division 1

IECEx ia

InMetro






OTHER

Submersible yes

Minimum Pack	6
---------------------	----------

Military yes

Package Code	C
--------------	---

FL1 STANDARD	HIGH
	183 LUMENS
	5h 45mins
	184m
	8480cd
	IPX7

ACCESSORIES