

9415Z0

9410L + SAFETY = 9415Z0 Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 530 lumens, the 9415Z0 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 272 meters. And it's loaded with innovative technology and features you have come to expect from Peli.

Safety certified for the most volatile work areas, the 9415Z0 LED Lantern is safe and one of the most compact, high output lanterns on the market. Certified to ATEX Zone 0 (Category 1)



DIMENSIONS

Length	8.75" (22.2 cm)
MATERIALS	
Body	Anti-static Impact Modified PC/PBT
O-Ring	EPDM

воау	Anti-static impact Modified PC/PBT	
O-Ring	EPDM	
Lens	Anti-static coated Polycarbonate (PC)	
Shroud	Anti-static Impact Modified PC/PBT	

COLOURS

High Visibility Yellow

LIGHT SPECS

Lamp Type

LED

POWER

Battery Size	С
Battery Type	NiMH
Battery Quantity	4
Batteries Included	yes
Rechargeable	yes
Charge Time	15 hrs
Battery Level Indicator	RGB LED
Volts	4.8v

WEIGHT

Weight With Batteries 58.2 oz (1650 gr)

SWITCH

Switch Type

CERTIFICATIONS

ATEX Zone 0 IECEx ia

OTHER

Minimum Pack Package Code 1 B

FL1 STANDARD	HIGH	LOW
	530 LUMENS	202 LUMENS
	4h 30mins	11h 30mins
	272m	166m
	18480cd	6914cd
	IPX4	

ACCESSORIES





9416 8056F Deck/Dash Charger Base Unit 12v Plug-in for Fast Charger



9418Z0 Replacement Battery



6061F Direct Wiring Rig for Fast Charger



6058H 220V Transformer (UK)

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-16-24