

1595TRVL

Air

Travel Case

Stop rummaging through old luggage at check-in lines or remote base camps and travel smarter with Peli™ Air Travel Cases. Lid organizers have zippered compartments for stowing larger items and see-through mesh pockets secure passports and cables. Packing cubes keep gear tightly bundled and allow you to arrange your gear by stacking or grouping side by side. Peli™ Air Travel Cases are also built for versatility. Just remove the packing cubes and replace with optional Trekpak™ dividers, padded dividers or Pick N Pluck™ foam interior solutions (available separately).

- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- · Quiet rolling stainless-steel bearing wheels
- *Check with your airline for exact measurement requirements
- Press and Pull™ Latches
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- · Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Limited Lifetime Warranty (Where applicable by law)
- Mid-size airline check-in case*



DIMENSIONS

Interior (L×W×D) 25.53 x 14.82" x 8.92 (64.8 x 37.6 x 22.7 cm) Exterior (L×W×D) 28.52 x 17.89" x 10.73 (72.4 x 45.4 x 27.3 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 6.92" (17.6 cm)

 Total Depth
 8.92" (22.7 cm)

 Int Volume
 1.95 ft³ (0.055 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM

PinsStainless SteelFoamPolyurethane

Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black Charcoal Indigo Oxblood

WEIGHT

 Weight Empty
 13.60 lbs (6.2 kg)

 Weight
 16.35 lbs (7.4 kg)

 Buoyancy
 148.37 lbs (67.3 kg)

 Weight With Organizers
 16.10 lbs (7.3 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & \mbox{-}60\ensuremath{\,^\circ}\mbox{F}\ (\mbox{-}51.1\ensuremath{\,^\circ}\mbox{C}) \\ \mbox{Maximum Temperature} & \mbox{1}60\ensuremath{\,^\circ}\mbox{F}\ (\mbox{7}1.1\ensuremath{\,^\circ}\mbox{C}) \\ \end{array}$

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 07-18-24