



AL1812-0602

For over 65 years Peli's roto-molded cases have been relied upon for an unmatched range of engineered solutions for the Military and Medical, Telecommunications and High Tech industries. Peli offers over 350 case sizes with unlimited case configurations using standard case options. Either build your own case or our engineers will customize a solution specific to your performance requirements.

Our roto molded cases pass MIL-STD 810D and E, MIL-STD 810E MIL-STD-210C, ASTM E96; FED-STD-101 and ATA 300 testing.

This level of performance ensures your equipment is safe from any unforeseen elements when deploying, transporting or storing your most valuable assets.

- Hardware attaches to molded-in metal inserts to provide pull-out strength and load spreading so hardware never fails.
- Molded-in ribs and corrugations offer case strength for secure and heavy weight stacking capacity
- Recessed hardware, with its engineered shoulder geometry, reduces shear forces that prevents lid separation after impact and controls pressure on the gasket to maintain a weatherproof seal
- Spigoli e bordi rinforzati per una maggiore protezione contro gli urti
- Costole di rinforzo, stampate e sagomate, per mantenere il contenitore stabile, in posizione verticale
- Struttura in un unico pezzo, stampata in polietilene leggero e ultrasistente agli urti



DIMENSIONI

| | |
|-----------------------------|--|
| INTERNO | 18.11 x 12.24" x 8.52 (46 x 31.1 x 21.6 cm) |
| ESTERNO | 21.00 x 15.25" x 10.25 (53.3 x 38.7 x 26 cm) |
| profondità coperchio | 2.57" (6.5 cm) |
| profondità fondo | 5.95" (15.1 cm) |
| profondità totale | 8.52" (21.6 cm) |
| volume interno | 1.09 ft ³ (0.031 m ³) |

MATERIALE

| | |
|--|--|
| corpo | RotoMolded Polyethylene |
| Fermo | Steel (Nickel-black Plated) |
| o-ring | Silicone Sponge |
| schiuma | No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined |
| gruppo di regolazione pressione | Aluminum |
| PRV Valve | .5 PSI Standard, Light Lift .25 PSI |
| maniglia | Heavy Duty Injection Molded Standard |
| Optional Handles | Stainless Steel Passivate and Stainless Steel Black |
| bulloneria | Yellow Carbon Steel Standard |
| Optional Hardware | Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black |

COLORI

■ Gray - 133 Fed Std
26270

IL PESO

peso 12.41 lbs (5.6 kg)

TEMPERATURA

temperatura minima -20°F (-28.9 °C)

temperatura massima 140°F (60 °C)

ALTRO

Militare sì

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24