



## IS2117-1103

ISP Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The new ISP Case from Pelican™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The patent pending system is compatible across 6 different case sizes from 4 to 25 cubic feet of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMIC containers, 463L pallets or sea containers, the ISP Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern there is no question where the next case belongs. The disc pattern bottom mates with the wave pattern on the case below, literally falling and locking into place. Cross-stacking builds incredibly tight loads that can save time with strapping or netting.

- Standard Features:
  - Removable Lid
  - Freebreathing
  - Black Carbon Steel, All Catch and Strike Hardware
  - 2 Large Injection Molded Comfort Grip handles
  - Colors: BLACK\_032, GREY\_133, OLIVE DRAB\_137, RED\_130, TAN\_250
  - Inter-Stacking Pattern Cases for NATO pallets, JMIC containers, 463L pallets or sea containers


- Configurable Features:
  - Hardware: Black Stainless Steel
  - Pressure Relief Valve (PRV) with Closed Gasket
  - Hinged Lid
  - Metal Handles: Black Stainless Steel
  - 2 Cable Catch locks per case
  - 2 Padlock Hasps per case
  - 3" X 5" Horizontal Card Holder
  - Front Labels, STD Labels and ATA Labels
  - Pressure Relief Valve
  - Humidity Indicator



## CONFIGURATIONS



**IS2117-1103**  
Standard



**IS2117-1103-No-Foam**  
No Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	21.00 x 17.00" x 14.00 (53.3 x 43.2 x 35.6 cm)
<b>Exterior (LxWxD)</b>	24.00 x 20.00" x 16.00 (61 x 50.8 x 40.6 cm)
<b>Lid Depth</b>	3.00" (7.6 cm)

<b>Bottom Depth</b>	11.00" (27.9 cm)
<b>Total Depth</b>	14" (35.6 cm)
<b>Int Volume</b>	2.89 ft <sup>3</sup> (0.082 m <sup>3</sup> )






## MATERIALS

---

<b>Body</b>	RotoMolded Polyethylene
<b>Latch</b>	Steel (Nickel-black Plated)
<b>O-Ring</b>	Silicone Sponge
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Purge Body</b>	Aluminum

## COLORS

---

 Black - 032 Fed Std 27040	 Olive Drab - 137 Fed Std 34096	 Gray - 133 Fed Std 26270	 Tan - 250 Fed Std 20372
 Red - 130 Fed Std 21105			

## WEIGHT

---

<b>Weight With Foam</b>	26.00 lbs (11.8 kg)
<b>Weight Empty</b>	20.00 lbs (9.1 kg)

## TEMPERATURE

---

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

## CERTIFICATIONS

---

**MIL-STD-810F**

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 08-16-24*