



iM2435

Storm

Top Loader Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Retractable extension trolley handle
- Two Press & Pull Latches
- In-line Wheels
- O-ring seal
- Lightweight Strong HPX® Resin
- Two stainless steel padlock protectors



CONFIGURATIONS



iM2435
Standard



iM2435-X0000
No Foam



iM2435-X0002
With Padded Dividers & Lid Organizer



iM2435-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	17.50 x 6.50" x 15.50 (44.5 x 16.5 x 39.4 cm)
Exterior (LxWxD)	18.63 x 9.25" x 16.50 (47.3 x 23.5 x 41.9 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	13.50" (34.3 cm)
Total Depth	15.5" (39.4 cm)
Int Volume	1.02 ft ³ (0.029 m ³)
Padlock Hole Diameter	0.37" (0.9 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)

Purge Body (Alt) Xenoy - Polyester/Polycarbonate blend
Purge Vent Gortex membrane

COLORS

■ Black

WEIGHT

Weight With Foam 11.15 lbs (5.1 kg)
Weight Empty 10.00 lbs (4.5 kg)
Buoyancy 56.70 lbs (25.7 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Extendable Handle yes
Master Pack 1
Military yes

ACCESSORIES



iM2435-FOAM
5 pc. Replacement Foam Set



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-17-24