



## 2460 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED Flashlight. The 2460 uses the 2469P Ni-MH batteries for extended burn time. It comes with a charger base unit that can be installed at home or work using the transformer, or in a vehicle through direct wiring or 12V plug-in.

- Built Pelican tough
- Rechargeable battery pack
- Super bright 1 watt LED beam
- Unconditional Lifetime Guarantee of Excellence
- **NOW WITH NEW UPGRADED SPECS**
- Waterproof



### DIMENSIONS

---

<b>Length</b>	7.00" (17.8 cm)
---------------	-----------------


### MATERIALS

---

<b>Body</b>	ABS
<b>O-Ring</b>	Ethylene Propylene
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	ABS
<b>Contact Spring Retainer</b>	Stainless Steel / Phosphore Bronze

### COLORS

---

 High Visibility Yellow
--

### LIGHT SPECS

---

<b>Lamp Type</b>	LED
------------------	-----

### POWER

---

<b>Battery Size</b>	AA
<b>Battery Type</b>	NiMH
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	3 hrs
<b>Volts</b>	4.8v

### WEIGHT

---

<b>Weight With Batteries</b>	7.8 oz (221 gr)
<b>Weight Without Batteries</b>	4.4 oz (125 gr)
<b>Packaged Weight</b>	1.4 oz (40 gr)

## SWITCH






<b>Switch Type</b>	One-handed Safety Switch
<b>Light Modes</b>	On / Off

## CERTIFICATIONS

**Class I, Division 2**  
**Class II, Division 2**

## OTHER

<b>Submersible</b>	yes
<b>Minimum Pack</b>	1
<b>Military</b>	yes
<b>Package Code</b>	C

FL1 STANDARD	HIGH
	183 LUMENS
	5h 0mins
	179m
	8050cd
	IPX7

## ACCESSORIES



**8056F**  
12v Plug-in for Fast Charger



**2467F**  
110V Transformer (USA)



**6061F**  
Direct Wiring Rig for Fast Charger



**2469P**  
Replacement Battery

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 07-17-24*