

1750 Protector Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Strong polyurethane wheels with stainless steel bearings

- Watertight, crushproof, and dustproof
- 3-piece foam set

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click[™] MOLLE Panels
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles
- *1500 EZ-Click $^{\mbox{\tiny M}}$ MOLLE Panels sold separately. Now available for purchase



CONFIGURATIONS



1750 Standard



1750WF With Foam



1750NF No Foam

DIMENSIONS

Interior (L×W×D)	50.38 x 13.33" x 5.33 (128 x 33.9 x 13.5 cm)
Exterior (L×W×D)	53.60 x 16.05" x 6.13 (136.1 x 40.8 x 15.6 cm)
Int Volume	2.07 ft ³ (0.059 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

COLORS

Black

WEIGHT

Weight With Foam	26.70 lbs (12.1 kg)
Weight Empty	21.00 lbs (9.5 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

OTHER

Nameplate

yes

ACCESSORIES



1500MP EZ-Click[™] MOLLE Panel



1500CI Corrosion Intercept Kit



1506TSA TSA Lock





1500D Desiccant Silica Gel



1753 Replacement O-ring

1751FS 3 pc. Replacement Foam Set

LGMT-001P Protector Case Roof Mount

1111 88 0000

1750PRS Re-set Kit



Document created on 04-26-25