



## CLASSIC-V-SERIES-9U

### Classic V

9U

- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U - 9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- Black stainless steel handles, and 1 comfort grip plastic handle on the 2" lid for rolling the case
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 2 edge casters on 5" lid
- RoHs compliant



### DIMENSIONS

<b>Exterior (LxWxD)</b>	45.80 x 27.00" x 24.30 (116.3 x 68.6 x 61.7 cm)
<b>Rack Height</b>	15.75" (40 cm)
<b>Rack Depth</b>	33.00" (83.8 cm)
<b>Interior Lid Depth</b>	2.50" (6.4 cm)
<b>Interior Back Lid Depth</b>	5.25" (13.3 cm)

### MATERIALS

<b>Body</b>	RotoMolded Polyethylene
<b>O-Ring</b>	Silicone Sponge
<b>Purge Body</b>	Aluminum
<b>Hardware</b>	Stainless Steel (Black Oxide) / RoHs Nickel Black
<b>Frame</b>	Steel (Clear Coated)

### COLORS

■ Black

### WEIGHT

<b>Weight</b>	72.00 lbs (32.7 kg)
---------------	---------------------

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

