

1200 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican TM Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



CONFIGURATIONS



1200 Standard



1200WF With Foam

DIMENSIONS

| Interior (L×W×D) | 9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm) |
|-----------------------|--|
| Exterior (L×W×D) | 10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm) |
| Lid Depth | 1.19" (3 cm) |
| Bottom Depth | 2.93" (7.4 cm) |
| Total Depth | 4.12" (10.5 cm) |
| Int Volume | 0.16 ft ³ (0.005 m ³) |
| Padlock Hole Diameter | 0.19" (0.5 cm) |

MATERIALS

| Body | Polypropylene | |
|------------|---------------------|--|
| Latch | ABS | |
| O-Ring | EDPM Medium Density | |
| Pins | Stainless Steel | |
| Foam | Polyurethane | |
| Purge Body | ABS | |
| Purge Vent | LM10411 | |
| | | |

COLORS

| Black Silver | Desert Tan Yellow | Orange | OD Green | |
|---------------------|----------------------|--------|----------|--|
| WEIGHT | | | | |
| Weight With Foam | 2.75 lbs (1.2 kg) | | | |
| Weight Empty | 2.55 lbs (1.2 kg) | | | |
| Buoyancy | 13.80 lbs (6.3 kg) | | | |
| Master Pack Weight | 19.00 lbs (8.6 kg) | | | |
| Habiel Fack Height | 19100 109 (010 kg) | | | |
| TEMPERATURE | | | | |
| Minimum Temperature | -40°F (-40 °C) | | | |
| Maximum Temperature | | | | |
| | | | | |
| OTHER | | | | |
| | 6 | | | |
| Master Pack | - | | | |

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 05-07-24