

1510 Protector Carry-On Case

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Pelican 1510 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Pelican 1510 Protector Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand.

- · Personalized nameplate service available
- Maximum airline carry on size*
- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- · Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- * Check with your airline for exact measurement requirements.



CONFIGURATIONS











1510WF With Foam



1510TPF TrekPak / Foam Hybrid

Standard

1514 With Padded Dividers

No Foam



1510TP With TrekPak Divider System

DIMENSIONS

Interior (L×W×D)	19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)
Exterior (L×W×D)	22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	5.79" (14.7 cm)
Total Depth	7.58" (19.3 cm)
Int Volume	0.96 ft ³ (0.027 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

pylene
r
ss Steel
olyurethane

1510NF



Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

COLORS

|--|--|--|

WEIGHT

Weight With Foam	13.60 lbs (6.2 kg)
Weight Empty	11.99 lbs (5.4 kg)
Buoyancy	64.15 lbs (29.1 kg)
Weight With TrekPak / Foam Hybrid	14.94 lbs (6.8 kg)
Master Pack Weight	32.43 lbs (14.7 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67 Def Stan 81-41

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	2
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



1511 4 pc. Replacement Foam Set

1510TPDIV Extra TrekPak Dividers



1513 Replacement O-ring



1507 Quick Mounts - set of 4



1515 Padded Divider Set



1506TSA TSA Lock



1519 Lid Organizer



1500D Desiccant Silica Gel



1510TPKIT TrekPak Case Divider Kit



1510MP EZ-Click[™] MOLLE Panel



1500CI Corrosion Intercept Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 05-04-24