



## 9415Z0

### 9410L + SAFETY = 9415Z0

#### Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 530 lumens, the 9415Z0 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 272 meters. And it's loaded with innovative technology and features you have come to expect from Peli.

Safety certified for the most volatile work areas, the 9415Z0 LED Lantern is safe and one of the most compact, high output lanterns on the market. Certified to ATEX Zone 0 (Category 1)




### DIMENSIONS

**Length** 8.75" (22.2 cm)

### MATERIALS

**Body** Anti-static Impact Modified PC/PBT  
**O-Ring** EPDM  
**Lens** Anti-static coated Polycarbonate (PC)  
**Shroud** Anti-static Impact Modified PC/PBT

### COLOURS

 High Visibility Yellow

### LIGHT SPECS

**Lamp Type** LED

### POWER

**Battery Size** C  
**Battery Type** NiMH  
**Battery Quantity** 4  
**Batteries Included** yes  
**Rechargeable** yes  
**Charge Time** 15 hrs  
**Battery Level Indicator** RGB LED  
**Volts** 4.8v

### WEIGHT

**Weight With Batteries** 58.2 oz (1650 gr)

### SWITCH

**Switch Type** Push Button

**Light Modes**






High / Low / Flashing

## CERTIFICATIONS

**ATEX Zone 0****IECEX ia**

## OTHER

**Minimum Pack  
Package Code**1  
B

FL1 STANDARD	HIGH	LOW
	530 LUMENS	202 LUMENS
	4h 30mins	11h 30mins
	272m	166m
	18480cd	6914cd
	IPX4	

## ACCESSORIES

**9416**


Deck/Dash Charger Base Unit

**8056F**

12v Plug-in for Fast Charger

**941820**

Replacement Battery

**6061F**Direct Wiring Rig for Fast  
Charger**6058H**

220V Transformer (UK)

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-17-24*