



# 1700

## Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3-piece foam set
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Hi-density foam tray option for 10 firearms
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



### DIMENSIONS

<b>Interior (LxWxD)</b>	35.76 x 13.73" x 5.35 (90.8 x 34.9 x 13.6 cm)
<b>Exterior (LxWxD)</b>	38.47 x 16.42" x 6.14 (97.7 x 41.7 x 15.6 cm)
<b>Int Volume</b>	1.52 ft <sup>3</sup> (0.043 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

### COLORS

 Black	 Desert Tan	 OD Green
---	--	--

### WEIGHT

<b>Weight With Foam</b>	16.85 lbs (7.6 kg)
<b>Weight Empty</b>	15.10 lbs (6.8 kg)

### TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
----------------------------	----------------

**Maximum Temperature** 210°F (98.9 °C)

OTHER

---

**Military** yes

ACCESSORIES

---



**1500MP**  
EZ-Click™ MOLLE Panel



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1703**  
Replacement O-ring

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 07-17-24*