

1550 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



DIMENSIONS

| Interior (L×W×D) | 18.63 x 14.18" x 7.72 (47.3 x 36 x 19.6 cm) |
|-----------------------|-----------------------------------------------|
| Exterior (L×W×D) | 20.66 x 17.20" x 8.40 (52.5 x 43.7 x 21.3 cm) |
| Lid Depth | 1.75" (4.4 cm) |
| Bottom Depth | 5.87" (14.9 cm) |
| Total Depth | 7.62" (19.4 cm) |
| Int Volume | 1.18 ft³ (0.033 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

28.35 lbs (12.9 kg)

MATERIALS

| Body | Polypropylene |
|------------|--------------------------------|
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |
| | |

COLORS

Master Pack Weight

| Black | Orange | Silver | Yellow | |
|------------------|---------------------|--------|--------|--|
| WEIGHT | | | | |
| Weight With Foam | 11.90 lbs (5.4 kg) | | | |
| Weight Empty | 10.58 lbs (4.8 kg) | | | |
| Buoyancy | 69.89 lbs (31.7 kg) | | | |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) | |
|---------------------|-----------------|--|
| Maximum Temperature | 210°F (98.9 °C) | |

CERTIFICATIONS

| IP67 | | |
|----------------|--|--|
| MIL C-4150J | | |
| Def Stan 81-41 | | |
| ATA 300 | | |

OTHER

| Master Pack | 2 |
|-------------|-----|
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1551 4 pc. Replacement Foam Set

1552 Pick N Pluck[™] Sections Only (set of 2)



1553 Replacement O-ring



1555 Padded Divider Set



1506TSA TSA Lock



1550PF Special Application Panel Frame



1500D Desiccant Silica Gel



1550TPKIT TrekPak Case Divider Kit



1510TPDIV Extra TrekPak Dividers



1507 Quick Mounts - set of 4



PL2 Padlock (2 pack)

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 07-17-24