



1150 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



DIMENSIONS

Interior (LxWxD)	8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm)
Exterior (LxWxD)	9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm)
Lid Depth	0.75" (1.9 cm)
Bottom Depth	2.87" (7.3 cm)
Total Depth	3.62" (9.2 cm)
Int Volume	0.1 ft³ (0.003 m³)
Padlock Hole Diameter	0.19" (0.5 cm)

MATERIALS

Body	Polypropylene
Latch	Polypropylene
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Blue	 Desert Tan	 Orange
 Silver	 Yellow		

WEIGHT

Weight With Foam	1.75 lbs (0.8 kg)
Weight Empty	1.61 lbs (0.7 kg)
Buoyancy	8.00 lbs (3.6 kg)
Master Pack Weight	13.95 lbs (6.3 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)









CERTIFICATIONS

IP67	
Def Stan 81-41	

OTHER

Master Pack	6
Military	yes

ACCESSORIES

				
1151 3 pc. Replacement Foam Set	1153 Replacement O-ring	1150PF Special Application Panel Frame	1150TPKIT TrekPak Case Divider Kit	1150TPDIV Extra TrekPak Dividers
				
1507 Quick Mounts - set of 4	1506TSA TSA Lock	1500D Desiccant Silica Gel		

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-05-24