



1600 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1600
Standard



1604
With Padded Dividers



1600NF
No Foam



1600TP
With TrekPak Divider System



1600WF
With Foam






DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm) |
| Exterior (L×W×D) | 24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm) |
| Lid Depth | 1.75" (4.4 cm) |
| Bottom Depth | 6.12" (15.5 cm) |
| Total Depth | 7.87" (20 cm) |
| Int Volume | 1.65 ft ³ (0.047 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | | | |
|--|--|--|--|
|  Black |  Desert Tan |  Orange |  Silver |
|  Yellow | | | |

WEIGHT

| | |
|--------------------|----------------------|
| Weight With Foam | 14.11 lbs (6.4 kg) |
| Weight Empty | 13.00 lbs (5.9 kg) |
| Buoyancy | 117.00 lbs (53.1 kg) |
| Master Pack Weight | 34.75 lbs (15.8 kg) |

TEMPERATURE

| | |
|---------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| |
|----------------|
| IP67 |
| MIL C-4150J |
| Def Stan 81-41 |
| ATA 300 |

OTHER

| | |
|-------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| 1601 4 pc. Replacement Foam Set | 1602 Pick N Pluck™ Sections Only (set of 2) | 1603 Replacement O-ring | 1605 Padded Divider Set | 1609 Lid Organizer |
|  |  |  |  |  |
| 1600TPKIT TrekPak Case Divider Kit | 1510TPDIV Extra TrekPak Dividers | 1507 Quick Mounts - set of 4 | 1506TSA TSA Lock | 1500D Desiccant Silica Gel |



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-26-24