



## 2410Z0 StealthLite™

Same features as the StealthLite™ 2400 but with the LED module that produces a true, bright collimated LED beam. The StealthLite™ 2410Z0 LED Zone 0 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells and certified to ATEX Zone 0 (Category 1).




### DIMENSIONS

<b>Length</b>	7.00" (17.8 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	Ethylene Propylene
<b>Lens</b>	Anti-static PMMA
<b>Shroud</b>	Anti-static Impact Modified PC/PBT
<b>Contact Spring Retainer</b>	Stainless Steel / Phosphore Bronze

### COLOURS

 High Visibility Yellow
--

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	4
<b>Volts</b>	6.0v

### WEIGHT

<b>Weight With Batteries</b>	7.3 oz (207 gr)
<b>Weight Without Batteries</b>	3.7 oz (105 gr)
<b>Packaged Weight</b>	8.4 oz (238 gr)

### SWITCH

<b>Switch Type</b>	One-handed Safety Switch
<b>Light Modes</b>	On / Off

## CERTIFICATIONS

**Peli**






**ATEX Zone 0**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

## OTHER

*Document created on 08-16-24*

**Minimum Pack** 6  
**Package Code** B

FL1 STANDARD	HIGH
	153 LUMENS
	5h 45mins
	165m
	6837cd
	IPX7

## ACCESSORIES