

9415

9410L + SAFETY = 9415

Everything that's great about the 9410L LED Lantern, plus safety certifications At just 3 pounds and 588* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 314 yards (288* meters). And it's loaded with innovative technology and features you have come to expect from Pelican. Whether you're on a USAR team or the 3rd shift at a refinery, you'll appreciate the compact size and high output of the new 9415 LED Lantern.

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market. 9415 LED Lantern: Lightweight, big LED performance you can trust. *Performance data is to FL 1 standards

- · Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Safety Certified Class I, Division I
- Approved to NFPA (National Fire Protection Association) 1901
- · Carrying Strap included



DIMENSIONS

Length 8.75" (22.2 cm)

MATERIALS

Body ABS O-Ring EPDM

Lens Polycarbonate (PC)

Shroud EXL

COLORS

High Visibility Yellow

LIGHT SPECS

Lamp Type LED

POWER

Battery TypeNiMHBattery Quantity4Batteries IncludedyesRechargeableyesCharge Time15 hrsBattery Level IndicatorRGB LEDVolts4.8v

WEIGHT

Weight With Batteries Weight Without

49.3 oz (1398 gr)

Weight Witho Batteries 0.0 oz (0 gr)

SWITCH

Switch Type Light Modes Push Button

High / Low / Flashing

CERTIFICATIONS

Class I, Division 1

OTHER

Minimum Pack Package Code 1 B

FL1 STANDARD	HIGH	
314	588 LUMENS	

314	588 LUMENS	224 LUMENS
	4h 30mins	11h 30mins
	288m	176m
	20792cd	7787cd
	IPX4	

LOW

ACCESSORIES







6057F 110V Transformer (USA)



6061FDirect Wiring Rig for Fast
Charger



8056F 12v Plug-in for Fast Charger



9418Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 07-17-24