9000
Light

Whether you keep it your car for roadside emergencies or to protect your essentials on kayaking or rafting trips, the Pelican 9000 Light is a unique solution to provide illumination and essential storage.
The 9000 Light provides general illumination of up to 300 lumens and has a maximum run time of 75 hours on the low setting. When set to flashing mode, it can run up to 24 hours and provide a safety beacon for roadside emergencies.
Under the light is a small compartment that can hold everyday-carry items, extra batteries, medical supplies, cell phones, or other small items. The case has a stand, so that it can stand flat on its own, and a hanging clip. This light is waterproof with an IP67 rating for use in wet conditions.

• 2-IN-1: LED light and case in one product
• POWER: The LED light can be set to high, medium, or low in both flashing and static modes. It has an output up to 300 lumens and a maximum run time of 75 hours.
• SAFETY: In flashing mode, it can run up to 24 hours and provide a safety beacon for roadside emergencies.
• SMART STORAGE: The case holds everyday-carry items, extra batteries, medical supplies, cellular phones, or other small items.
• WATERPROOF: IP67 Rated* to protect items from water, dirt, and dust
• *Case can be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters
• VERSATILITY: Hang, hook, or stand the light case for hands-free use. Carabiner included.
• APPLICATION: Use for outdoor activities, such as kayaking, hiking, camping and overlanding, or for a small emergency preparedness kit.

DIMENSIONS

Length	8.11" (20.6 cm)

MATERIALS

Body	ABS / Polycarbonate (PC)
O-Ring	Silicone

COLORS

■ Black

LIGHT SPECS

Lamp Type	LED
Lamp Life	10000 hrs

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	4
Batteries Included	yes
Volts	6.0v

WEIGHT

Weight With Batteries	21.6 oz (612 gr)
Weight Without Batteries	18.2 oz (516 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Medium / Low / Signaling

FL1 STANDARD	HIGH	MEDIUM	LOW
	300 LUMENS	165 LUMENS	35 LUMENS
	3h 20mins	9h 30mins	75h 0mins
	25m	20m	11m
	147cd	80cd	17cd
	IPX7		

Document created on 07-17-24