



1500 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1500
Standard



1504
With Padded Dividers



1500NF
No Foam



1500WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 16.75 x 11.18" x 6.12 (42.5 x 28.4 x 15.5 cm) |
| Exterior (L×W×D) | 18.50 x 14.06" x 6.93 (47 x 35.7 x 17.6 cm) |
| Lid Depth | 1.81" (4.6 cm) |
| Bottom Depth | 4.31" (10.9 cm) |
| Total Depth | 6.12" (15.5 cm) |
| Int Volume | 0.66 ft ³ (0.019 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |

Purge Vent

3 Micron Hydrophobic Non-Woven

COLORS

- | | | | |
|--|--|--|---|
|  Black |  Desert Tan |  Orange |  OD Green |
|  Silver |  Yellow | | |

WEIGHT

- | | |
|---------------------------|---------------------|
| Weight With Foam | 7.94 lbs (3.6 kg) |
| Weight Empty | 7.13 lbs (3.2 kg) |
| Buoyancy | 50.00 lbs (22.7 kg) |
| Master Pack Weight | 40.65 lbs (18.4 kg) |

TEMPERATURE

- | | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

- IP67**
- MIL C-4150J**
- Def Stan 81-41**
- ATA 300**

OTHER

- | | |
|--------------------|-----|
| Master Pack | 4 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1501
3 pc. Replacement Foam Set



1503
Replacement O-ring



1505
Padded Divider Set



1508
Photographer's Lid Organizer



1509
Lid Organizer



1500PF
Special Application Panel Frame



1500TPKIT
TrekPak Case Divider Kit



1500TPDIV
Extra TrekPak Dividers



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500MP
EZ-Click™ MOLLE Panel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 06-30-24