

1607

Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 45 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- · Business card holder
- · Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- · Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- · Made in the USA



CONFIGURATIONS



1607 Standard



1607NF No Foam



1607WDWith Padded Dividers



1607WF With Foam

DIMENSIONS

Interior (L×W×D) 21.05 x 15.81" x 11.63 (53.5 x 40.2 x 29.5 cm) Exterior (L×W×D) 24.13 x 18.80" x 13.25 (61.3 x 47.8 x 33.7 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 9.60" (24.4 cm)

 Total Depth
 11.6" (29.5 cm)

 Int Volume
 2.24 ft³ (0.063 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS



Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS

Black Orange Silver Yellow

WEIGHT

 Weight With Foam
 16.10 lbs (7.3 kg)

 Weight Empty
 13.20 lbs (6 kg)

 Buoyancy
 178.00 lbs (80.7 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & -60\,^{\circ}\mbox{F} \ (-51.1\,^{\circ}\mbox{C}) \\ \mbox{Maximum Temperature} & 160\,^{\circ}\mbox{F} \ (71.1\,^{\circ}\mbox{C}) \\ \end{array}$

OTHER

Wheels 2

ACCESSORIES



Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-03-24