

1660 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4 strong polyurethane wheels with stainless steel bearings
- · Large 2-person fold down handles
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck[™] with convoluted lid foam
 Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1660 Standard



1664 With Padded Dividers



1660NF No Foam



1660WF With Foam

DIMENSIONS

Interior (L×W×D)	28.20 x 19.66" x 17.63 (71.6 x 49.9 x 44.8 cm)
Exterior (L×W×D)	31.59 x 22.99" x 19.48 (80.2 x 58.4 x 49.5 cm)
Lid Depth	3.50" (8.9 cm)
Bottom Depth	14.14" (35.9 cm)
Total Depth	17.64" (44.8 cm)
Int Volume	5.66 ft³ (0.16 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

COLORS

|--|--|

WEIGHT

Weight With Foam	42.16 lbs (19.1 kg)
Weight Empty	34.16 lbs (15.5 kg)
Buoyancy	365.00 lbs (165.6 kg)
Master Pack Weight	49.00 lbs (22.2 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67	
Def Stan 81-41	

OTHER

Wheels	4
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



1661 5 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1662 Pick N Pluck[™] Sections Only (set of 3)



TSA Lock

1506TSA



1663 Replacement O-ring



1500D Desiccant Silica Gel



1665 Padded Divider Set



1500Cl Corrosion Intercept Kit



1669 Photo/Lid Organizer

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-06-24