



# 1465EMS

## Air

### EMS Case

When every second counts, you can depend on the new Pelican™; Air 1465EMS case to keep you moving through the harshest terrain. Weighing in at only 13.2 pounds (empty) and crushproof, the Pelican™ Air 1465EMS case minimizes strain while protecting vital medical supplies without weighing you down.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Removable trays are easy to wipe down to keep sanitized
- Three tier customizable pullout trays give you the flexibility to organize
- Storage bracket keeps used and sharp objects contained
- Press & Pull latches have been tested for extreme pressure and impact situations
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2</sup>™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- \*Sharps container not included
- Waterproof, crushproof, dustproof
- Made in the USA



## DIMENSIONS

<b>Interior (LxWxD)</b>	18.62 x 9.99" x 10.93 (47.3 x 25.4 x 27.8 cm)
<b>Exterior (LxWxD)</b>	20.83 x 12.62" x 12.75 (52.9 x 32.1 x 32.4 cm)
<b>Lid Depth</b>	4.94" (12.5 cm)
<b>Bottom Depth</b>	5.99" (15.2 cm)
<b>Total Depth</b>	10.93" (27.8 cm)
<b>Int Volume</b>	1.18 ft <sup>3</sup> (0.033 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

## MATERIALS

<b>Body</b>	Proprietary Polypropylene Blend
<b>Latch</b>	ABS
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven
<b>Tray</b>	ABS

## COLORS

 Orange

## WEIGHT

**Weight** 13.30 lbs (6 kg)

## TEMPERATURE

---

**Minimum Temperature** -60°F (-51.1 °C)

**Maximum Temperature** 160°F (71.1 °C)

## ACCESSORIES

---



**1500CI**  
Corrosion Intercept Kit

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 03-11-25*