



2315

The hazard horizon is bright. With Class I, II, III - Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

Pelican™ 2315 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Resistencia Pelican
- 2 pilas alcalinas AA (incluidas)
- Clip integrado
- Interruptor trasero para un uso puntual o continuado
- Clase I, II, III - División 1 / IECEx ia Certificación de seguridad
- Certificado de protección IPX8 resistente el agua (1 m)
- Soporte para casco (incluido)




DIMENSIONES

longitud	6.22" (15.8 cm)
-----------------	-----------------

MATERIALES

cuerpo	ABS
anillo de sellado de neopreno	NBR
lente	PC
cubierta	ABS
Clip	ABS

COLORES

 High Visibility Yellow
--

LIGHT SPECS

tipo de sistema de iluminación	LED
---------------------------------------	-----

POWER

tamaño de las pilas	AA
tipo de pilas	Alkaline
cantidad de pilas	2
pilas incluidas	sí
voltios	3.0v

PESO






peso con las pilas	4.6 oz (130 gr)
peso sin las pilas	2.8 oz (79 gr)

SWITCH

tipo de interruptor Momentary Push Button
modos de iluminación High

CERTIFICACIONES

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEX ia

FL1 STANDARD	HIGH
	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-04-25