



3765PL

Right Angle Light

- Compact and Lightweight
- NFPA Compliant (National Fire Protection Agency) 1901
- Also Operates on 4 Standard AA Alkaline Batteries




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 5.36" (13.6 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|--------------------------------------|
| Body | ABS |
| O-Ring | Buna-N |
| Lens | Polycarbonate (PC) |
| Shroud | Photo luminescent Polycarbonate (PC) |
| Clip | Xenoy |

COLORS

 High Visibility Yellow

LIGHT SPECS

| | |
|----------------------------|-----|
| Lamp Type | LED |
| Lamp Secondary Type | LED |

POWER

| | |
|--------------------------------|---------------|
| Battery Size | AA |
| Battery Type | NiMH |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Rechargeable | yes |
| Charge Time | 3 hrs 30 mins |
| Battery Level Indicator | 3 Blue LEDs |
| Volts | 4.8v |

WEIGHT

| | |
|------------------------------|------------------|
| Weight With Batteries | 14.6 oz (414 gr) |
|------------------------------|------------------|

Weight Without Batteries

11.0 oz (312 gr)

SWITCH

Switch Type

Push Button

Light Modes

High / Low / Flashing

CERTIFICATIONS

Class I, Division 1

Class I, Division 2






OTHER

Minimum Pack

1

Package Code

B

| FL1 STANDARD | HIGH | LOW | DOWNCAST | FLASHING |
|---|---------------|---------------|-----------------|-----------------|
|  | 237 LUMENS | 113 LUMENS | 32 LUMENS | 140 LUMENS |
|  | 3h 0mins | 6h 30mins | 14h 0mins | 9h 0mins |
|  | 301m | 193m | 28m | 274m |
|  | 22720cd | 9354cd | 192cd | 18784cd |
|  | IPX4 | | | |

ACCESSORIES



3769
Replacement Battery



2467F
110V Transformer (USA)



6061F
Direct Wiring Rig for Fast Charger



8056F
12v Plug-in for Fast Charger

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 01-14-25