

# 1495 Protector Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- 3 dial combination lock included
- Fits up to 17" laptops
  Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps
- water out • Easy open double-throw latches
- Fold down over-molded handle
- Lifetime Guarantee of Excellence
- Padded shoulder strap
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Stainless steel padlock protectors



### CONFIGURATIONS



1495 Standard



1495NF No Foam



1495WF With Foam

### DIMENSIONS

| Interior (L×W×D)      | 18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm)  |
|-----------------------|---|
| Exterior (L×W×D)      | 21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm) |
| Lid Depth             | 1.12" (2.8 cm)                                |
| Bottom Depth          | 2.68" (6.8 cm)                                |
| Total Depth           | 3.8" (9.7 cm)                                 |
| Int Volume            | 0.55 ft³ (0.016 m³)                           |
| Padlock Hole Diameter | 0.25" (0.6 cm)                                |

#### MATERIALS

| Body   | Polypropylene   |
|--------|-----------------|
| Latch  | ABS             |
| O-Ring | Polymer         |
| Pins   | Stainless Steel |

| Foam       | 1.3 lb Polyurethane            |
|------------|--------------------------------|
| Purge Body | ABS                            |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

### COLORS

Black

Desert Tan

## WEIGHT

| Weight With Foam   | 8.37 lbs (3.8 kg)   |  |
|--------------------|---------------------|--|
| Weight Empty       | 7.23 lbs (3.3 kg)   |  |
| Buoyancy           | 45.15 lbs (20.5 kg) |  |
| Master Pack Weight | 23.00 lbs (10.4 kg) |  |

### TEMPERATURE

| Minimum Temperature | -40°F (-40 °C)  |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

### CERTIFICATIONS

IP67 Def Stan 81-41

### OTHER

| Master Pack | 2   |
|-------------|-----|
| Nameplate   | yes |

### ACCESSORIES



1472

Shoulder Strap



**1481** 3 pc. Replacement Foam Set



1500D Desiccant Silica Gel



1500CI Corrosion Intercept Kit



1483 Replacement O-ring



1507 Quick Mounts - set of 4



1506TSA TSA Lock

Document created on 05-28-24